

ADA4605—the Blue Fluorescent Organic Pigment

Description

Organic pigment—this product has a low toxicity to aquatic organisms and presents little to no immediate hazard to people if released or spilled. This pigment has a high solvent and thermal stability, but can be destroyed through any further reduction in particle size (shearing or milling). Exposure to acids may cause product degradation.


Product Properties

Composition and Appearance:	98-100% (w/w) Organic pigment
Ash:	0.09-1.4% (typical property)
Volatiles:	0.4%
Melting point:	202-205 °C
Fluorescence Emission (λ_{max}):	453 nm
Excitation (λ_{max}) :	365 nm
Particle size (Microtrac X-100:	$d_{10} = min. 15 \mu, d_{50} = max. 33 \mu, d_{95} = max. 60 \mu$
Lightfastness:	Good

Solubility

Soluble: Toluene, Mineral Oil (1.0% w/ heating), Propylene Glycol (0.10%) Partially Soluble: Acetone, EtOAc Slightly Soluble: EtOH Insoluble: Water

Excitation (left) and Emission Spectrum (right)



All applications using this product should be thoroughly tested prior to approval for production.

The information herein is believed to be reliable and is to assist customers in determining whether our products are suitable for their applications. However, no warranty, express or implied, is made as to its accuracy or completeness and none is made as to fitness of this material for any purpose. Our products are intended for sale to industrial and commercial customers. We request that customers inspect and test our products before use and satisfy themselves as to contents and suitability. Nothing herein shall constitute any other warranty, express or implied, including any warranty of merchantability or fitness, nor of protection from any law or patent to be inferred. All patent rights are reserved. The exclusive remedy for all proven claims is replacement of our materials and in no event shall we be liable for special, incidental, or consequential damages. We shall not be liable for damages to person or property resulting from its use. Consult the Material Safety Data Sheet for additional information.

H.W. Sands Corp. | 1003 W. Indiantown Rd. Suite 215 | Jupiter, FL 33458 | Tel: (561) 743-8090 | Fax: (561) 743-4088 | email: customerservice@hwsands.com | www.hwsands.com